

# **bizhub 4700**i Black & White single function printer

# bizhub 4700i SPECIFICATION & INSTALL GUIDE RETHINK IT



Giving Shape to Ideas

Table of Contents	
Specifications	3
Duty Cycle	5
Environmental Requirements	6
Basic Configuration	6
Space Requirements	7
Accessories	8
Print Controller (Standard)	13
Print Drivers	13
Security	14
Software Tools	14
Paper Considerations	15
Paper Weight Conversion Chart	15
Paper Type Specifications	16
How to Build a System	18
Accessory Options	19



### **BIZHUB 4700I SPECIFICATIONS**

TYPE	PRINTER
Photoconductor	OPC
Developing System	Dry-type dual-component HMT developing
Resolution	1200 x 1200 dpi, 600 x 600 dpi
Paper	Thin Paper (16 lb to 20 lb)
	Plain Paper (20 lb to 28 lb)
	Plain Paper +(24.75 lb to 28 lb)
	Thick Paper 1 (24.25 lb to 32 lb)
	Thick Paper 2 (32 lb to 53 lb)
	Recycled Paper (20 lb to 28 lb)
	Special Paper (20 lb to 28 lb)
	Letterhead (20 lb to 28 lb)
	Color Paper (20 lb to 28 lb)
	Envelopes, label sheets, postcards
Print Sizes	1st Tray:
	3.9" x 5.8" to 8.5" x 11.7"
	Bypass Tray:
	3.5" x 5.8" to 8.5" x 14"
Paper Tray Capacity	1 <sup>st</sup> Tray:
	Thin Paper/Plain Paper/Recycled Paper/Special Paper/Color Paper/1-Sided Special Paper: 500 sheets
	Thick Paper 1/12: 20 sheets
	Envelopes: 30 sheets
	Label sheets: 20 sheets
	Postcards: 20 sheets
	Bypass Tray:
	Plain Paper/Recycled Paper/Special Paper/Letterhead/Color Paper/
	1-Sided Special Paper: 100 sheets
	Thick Paper 1/2/Postcards: 20 sheets
	Envelopes: 10
	Label Sheets: 20 sheets
	Postcards: 20 sheets
Warm-Up Time	Less than 18 seconds (at room temperature/73° F)

# **BIZHUB 4700I SPECIFICATIONS**

DESCRIPTION	DESCRIPTION
Image Loss Width	Leading edge: 0.17"
	Trailing edge: 0.17"
	Rear edge: 0.17"
	Front edge: 0.17"
First Print	7.4 sec. or less
Print Speed*	Plain paper: 50 pages/min
(Simplex/Duplex)	Thick 1/Thick 2: 20 sheets/min.


# **BIZHUB 4700I SPECIFICATIONS**

TYPE	DIGITAL PRINTER
Power Requirements	110V, 60 Hz.
Power Consumption	1450 W or less
TEC Value	.81 kWh
Dimensions (with control panel)	16.5" (W) x 20.8" (D) x 18.6" (H)
Space requirements*	33.6" (W) x 35.4" (D) x 18.6" (H)
Memory	4 GB; 8 GB Micro SD
Weight	Approx. 64 lb.
* The indicated space requirer	nents represent the space required to pull out the paper tray and the tray extension of the bypass tray and with the ADE open

\* The indicated space requirements represent the space required to pull out the paper tray and the tray extension of the bypass tray and with the ADF open.

### **DUTY CYCLE**

### bizhub 4700i Up to 120,000 Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on continual basis.



## **ENVIRONMENTAL REQUIREMENTS**

ТҮРЕ	DESCRIPTION
Temperature	50° F to 90° F
Humidity	15% to 85%
Noise During Operation	73.3 dB or less
Noise During Standby	32 dB or less

### **ELECTRICAL REQUIREMENTS**

TYPE	DESCRIPTION	
Line Options	Dedicated	NEMA Diagram for 5-15R
Voltage	110 V/120 to 127V	
Amperage	12A	
Cycles	60	
NEMA Part No.	5-15R	
Cord Length	6.6 ft.	
Noto: The main electrical outlet	must be located within 6.6 feet from the right rear	corpor of the hizbub 4700i main unit


Note: The main electrical outlet must be located within 6.6 feet from the right rear corner of the bizhub 4700i main unit.

### **SAMPLE CONFIGURATION**




### **SPACE REQUIREMENTS**

### **bizhub** 4700i



# bizhub 4700i with options



7

### ACCESSORIES

AUTOMATIC DUPLEX UNIT (STANDARD)

Supported Paper Type	Thin Paper (14 lb to 15.5 lb)
	Plain Paper (16 lb to 24 lb)
	Thick Paper 1 (24.25 lb to 32 lb)
	Thick Paper 1+ (32.25 to 41.75 lb)
	Thick Paper 2 (42 lb to 55.5 lb)
	Recycled Paper (16 lb to 24 lb)
Supported Paper Size	4.7" x 8.8" to 8.5" x 14"
Power Requirements	Supplied from main unit
	* There are six Foolscap sizes: 220 x 330 mm (L), 8.5" x 13.5", 8.5" x 13" (L), 8.25" x 13 (L), 8.12" x 13.25" (L) and 8" x 13" (L).
	Any one of these sizes can be selected. For details, please consult with your authorized Konica Minolta Service representative.

### PF-P21 PAPER FEED CABINET

Туре	1 x 500 sheet drawer
Supported Paper Types Thin Paper (16 lb bond to 20 lb bond), Plain Paper (20 lb bond to 28 lb bond), Recycled Paper (20 lb to 28 lb),	
	Letterhead (16 lb bond to 24 lb bond), Colored Paper (16 lb bond to 24 lb bond)
Supported Paper Size	8.5" x 14" to 5.8" x 8.25", letter and legal only
Paper Capacity	500 sheets (21 lb)
Power Requirements	Supplied from main unit.
Weight	Approximately 17.4 lb

### PF-P25 HEIGHT ADJUSTMENT UNIT

Туре	Base (without storage), Increases height of the machine. Suggested if the machine is configured with the DK-P05 and fewer than two
	PF-P21 Paper Feeder Cabinets.
Dimensions (W x D x H)	14.3" x 15.1" x 5.8"
Weight (Approx.)	8.6 lb

# ACCESSORIES

DK-P05 COPY DESK

Туре	Storage drawer only
Function	Storage of accessories, paper, supplies, etc. Brings machine to working height.

#### UK-221 WIRELESS NETWORK ADAPTER

Туре	Miscellaneous Option
Function	Provides wireless connectivity

### EK-P08 USB HOST/LOCAL INTERFACE

Internal Component
Provides Type A USB port. Required for installation of an authentication unit or
external keyboard.

#### EK-P09 USB HOST/LOCAL INTERFACE

Туре	Internal Component
Function	Provides Type A USB port and Bluetooth connectivity. Required for installation of an
	authentication unit or external keyboard.

#### EK-P10 NFC KIT

Туре	Internal Component
Function	Provides Near Field Communications capabilities.

#### AU-205H IC CARD READER

Dimensions (W x H x D)	2.8" x 3.7" x 0.6"	
Host Interface	USB 2.0 (also compliant with USB 1.1)	
Power Supply	Supplied from USB Port	
Card Protocols	HID PROX, HID Indaia, EM ProxLow Frequency (125 kHz)	
Card Protocols	CCID: MIFARE Classic™ 1K/4K, Ultra Light, Ultra Light C, Plus, High Frequency	
	(13.5 MHz) MIFARE DESFire™ 0.6, MIFARE DESFire™ EV1, IC Card, iCLASS SE/SR®,	
	MIFARE SE™, DESFire EV1 SE, T=CL, ISO 14443 A with up to 848 kbps transmission	
	rate (depending on card1), ISO 15693 with up to 26 kbps transmission rate	
	(depending on card)	
	Keyboard Wedge: MIFARE™ Classic 1K/4K, Ultra Light, Ultra Light C, Plus (Security	
	Level 1), MIFARE DESFire™ 0.6, MIFARE DESFire™ EV1 (MAC/DES/3DES/3K3DES/	
	AES), IC Card, iCLASS SE/SR <sup>®</sup> , MIFARE SE™, DESFire EV1 SE	

9

# ACCESSORIES

MK-P08 MOUNT KIT

Туре	Internal Component
Function	Required for internal installation of AU-205H

#### FS-P04 OFF-LINE STAPLER

Туре	Stapling (off-line)	
Staple Capacity	20 sheets (90 gsm)	
Power Supply	From device	
Staples	SK-501	
Dimensions (W x H x D)	4.3" x 4.6" x 2.9"	
Weight	Approx. 2 lb	
Function	Provides finishing capabilities. Can be installed on working table WT-P03 or separately.	

### KP-P03 KEYPAD

Туре	10-key Pad
Function	Provides hard keys for entering numeric values

#### EXTERNAL KEYBOARD

Гуре	QWERTY Keyboard	
Function	Computer-type keyboard for alphanumeric data entry. Requires KH-P02 Keyboard Holder	
KH-P02 KEYPAD HOLDER		
уре	Mount Kit	
unction	Required for installation of External Keyboard	





# PRINT CONTROLLER (STANDARD)

Туре	Internal Type
CPU	SoC S800 (1.6 GHz)
Memory	4 GB
Print Speed (BW)	50 ppm Letter
Print Resolution	600 x 600 dpi, 1200 x 1200 dpi
PDL	PCL6, PS 3 Emulation, XPS 1.0 Emulation, PDF 1.7 Emulation, Epson FX-850 Emulation
Font	PCL Resident Fonts: 80 Scalable Fonts plus 12 Bitmapped Fonts
	PS3 Emulation Resident Fonts: 137 Scalable Fonts
Interface	Standard Ethernet (10Base-T/100Base-TX/1000Base T), Hi-Speed USB, 1.1 2.0, 3.0; USB Host, Interface Support for Ethernet SNAP, Ethernet II,
	Ethernet 802.3, or 802.2

### **PRINT DRIVERS**

PCL 6	Windows 7/8.1/10 (32-bit and 64-bit)
PostScript 3 Emulation	Windows Server 2008 (32-bit and 64-bit)
	Windows Server 2008 R2/2012/2012 R2/2016/2019 (64-bit)
	Mac OSX 10.10/10.11/10.12/10.13/10.14 (PostScript only)
	Red Hat Enterprise Linux 5 or later
XPS	Windows 7/8.1/10
	Windows Server 2008/2008 R2/ 2012/2012 R2/2016 x64

### **SOFTWARE TOOLS**

Aanagement Tools	bizhub vCare
	Dispatcher Suite
	Konica Minolta Mobile Print for iOS, Konica Minolta Mobile Print for Android, Konica Minolta Mobile Print for Windows
	Konica Minolta Print Service, Konica Minolta Print Service
	PageScope My Print Manager
	PageScope Net Care Device Manager, PageScope Account Managerm, PageScope Authentication Manager, PageScope My Panel Manager
	vCare, bizhub Remote Panel, Device Plug-in for PageScope Enterprise Suite
	HDD BackUp Utility, Log Management Utility, Font Management Utility, Panel Customize Tool, License Install Utility
	Web Connection, Mopria for Android, Download Manager, Data Administrator, Remote Deployment Tools, Box Operator, Print Status Notifier
User Tools	Direct Print, Konica Minolta Mobile Print for iPhone/iPad, Konica Minolta Mobile Print for Android, Konica Minolta Mobile Print for Windows
	WLAN Setup Wizard
	Remote Deployment Tools
	Net Care Device Manager
Network & Device Management	Driver Packaging Utility

# SECURITY

Because information assets are	1) Prevent Leaks of proprietary, confidential or personal information
critical, a company needs to	2) Prevent unauthorized use of equipment
effectively protect against the many	3) Effective data encryption
security risks it faces.	4) Protect data from being altered, duplicated or deleted
	5) Prevent unauthorized access to data via the Internet
	6) Protect against cyber attacks
	7) Manage log history
Protective Functions	Active Directory
	Enterprise Security (802.1x)
	• Secure Print
	• LDAP
	• SSL/TLS
	• IPSec

### **SOFTWARE TOOLS**

Network, Device Management	Data Administrator
and User Tools	Download Manager
	Print Status Notifier
	Driver Packaging utility
	Mobile Print
	Net Care Device Manager
	Web Connection
	Enterprise Suite Plug-in
	Account Manager
	Authentication Manager
	My Print Manager
	Box Operator
	Driver Packaging Utility
	Lock Job (when printing confidential documents)
	Protect data by requiring department name and 8-digit password
	Account Track • HDD Lock • Prevent Unauthorized Use
	Operation Log with 2,000-event memory
	PDF Scan Encryption
	Protective Functions
	Network Authentication

# **PAPER CONSIDERATIONS**

PAPER SIZE CONVERSION CHART

Paper	Letter	Letter R	Legal	Statement	Statement R
Measurement	8.5" x 11"	11" x 8.5"	8.5" x 14"	5.5" x 8.5"	8.5" x 5.5"

## **PAPER WEIGHT CONVERSION CHART**

								C	ALIPER
gsm	Bond	Offset	Cover	Tag	Index	Point	Bristol	inches	mm
60.20	16	40	22	37	33	3.2	27.4	0.0032	0.081
67.72	18	45	24	41	37	3.6	30.9	0.0036	0.092
75.20	20	50	28	46	42	3.8	34.3	0.0038	0.097
90.30	24	60	33	56	50	4.8	41.2	0.0048	0.120
105.35	28	70	39	64	58	5.8	48.1	0.0058	0.147
109.11	29	73	40	62	60	6.0	49.8	0.0060	0.152
116.63	31	81	45	73	66	6.1	53.2	0.0061	0.155
131.68	35	90	48	80	74	6.2	60.1	0.0062	0.157
135.45	36	90	50	82	75	6.8	61.8	0.0068	0.173
146.73	39	100	54	90	81	7.2	67.0	0.0072	0.183
150.50	40	100	56	93	83	7.3	68.7	0.0073	0.185
161.78	43	110	60	100	90	7.4	73.8	0.0074	0.188
165.55	44	110	61	02	92	7.6	75.5	0.0076	0.193
176.83	47	120	65	108	97	8.0	80.7	0.0078	0.198
199.41	53	135	74	122	110	9.0	91.0	0.0085	0.216
203.17	54	137	75	125	113	9.0	92.7	0.0090	0.229
218.22	58	146	80	134	120	9.5	99.6	0.0092	0.234
244.56	65	165	90	150	135	10.0	111.6	0.0095	0.241
252.08	67	170	93	156	140	10.5	115.1	0.0100	0.250
270.90	72	183	100	166	150	11.0	123.7	0.0110	0.289
285.95	76	192	105	175	158	13.0	130.5	0.0130	0.330
308.52	82	208	114	189	170	14.0	140.8	0.0140	0.356
312.00	87	220	120	200	180	15.0	142.4	0.0150	0.380
385.06	105	267	146	244	220	18.0	175.8	0.0175	0.445

# PAPER TYPE SPECIFICATIONS

Thin Paper	Paper weighing between 16 lb. to 20 lb. bond. It can be fed via any paper tray, except the bypass tray.
Nermal (Diain Danar)	Normal paper is used for copying in general and is called "PPC paper." The normal paper is usually not a recycled paper. Specify [Normal] to the tray to
Normal (Plain Paper)	which the normal paper or the recycled paper is loaded for copying.
Recycled Paper	Recycled Paper is identified as recycled paper along with a designation as to the percentage of the paper that is actually made from recycled materials
	Generally speaking, these devices will support recycled paper weighing between 20 lb and 28 lb bond.
Thick Paper 1	Thick Paper 1 is paper weighing between 28 lb and 32 lb bond It can be fed via any paper tray.
Thick Paper 2	Thick Paper 2 is paper weighing between 32 lb and 53 lb bond. It can be fed via any paper tray.
Special Paper	A thin or other specialty type paper that falls within the paper weight specification and appears on the Recommended Paper Stock List.
Envelopes	Specify (Envelope) for bypass tray.
Postcards	A Postcard is defined as a rectangular piece of the thick paper or thin cardboard. This product series supports 4" x 6" size postcards. Postcards are fed only via the Bypass Tray.

#### PAPER TYPE SPECIFICATIONS CON'T

Class.	Weight	Brand of Paper	Size
Plain Paper — Color			
Plain Paper	20 lb. Bond (75 gr)	Domtar Recycled Copy(30% Post Consumer)	8.5" x 11"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	8.5" X 11"
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	11″ X 17″
Plain Paper	22 lb. Bond(80 gr)	Konica Minolta CF Paper	12" X 18"
Plain Paper	24 lb. Bond (89 gr)	SMART Carnival Stellar White	8.5" x 11"
Plain Paper	24 lb. Bond (89 gr)	SMART Carnival White	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	SMART Synergy Bond 25% Cotton	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	Domtar Microprint Laser	8.5" x 11"
Plain Paper	24 lb. Bond (90 gr)	Mohawk Color Copy 98 Bright White	8.5" x 11"
Thick 1	28 lb. Bond(105 gr)	Konica Minolta CF Paper	8.5" X 11"
Thick 1	28 lb. Bond(105 gr)	Konica Minolta CF Paper	11" X 17"
Thick 1	28 lb. Bond (105 gr)	Konica Minolta CF Paper	12" X 18"
Thick 1	28 lb. Bond (105 gr)	Domtar Microprint Color Copy	8.5" x 11"
Thick 1	32 lb. Bond(120 gr)	Hammermill Color Copy	8.5" X 11"
Thick 1	32 lb. Bond (120 gr)	Hammermill Color Copy Paper – Photo White	8.5" x 11"
Thick 2	60 lb. Cover(163 gr)	Hammermill Color Copy	8.5" X 11"
Plain Paper — B & W			
Plain Paper	20 lb. Bond (75 gr)	Hammermill Tidal MP	8.5" X 11"
Double-Sided Glossy			
Thick 1	32 lb. Bond (120 gr)	Mohawk Color Copy Gloss Pure White	8.5" x 11"
Thick 1	80 lb. Text (118 gr)	Sappi Opus Gloss	8.5" x 11"
Thick 1	90 lb. Text (133 gr)	SMART Kromekote Laser High Gloss Coated Two Sides*	8.5" x 11"
Envelopes			
Envelope	24 lb.	Preservation Wove 5789 #6 3/4	3.85" x 6.5" (98 x 165 mm)
* Paper cannot be used in a	high humidity environment.		

# HOW TO BUILD A SYSTEM FOR THE BIZHUB 4700I DIGITAL PRINTER (FROM START TO FINISH)

#### STEP 1: BASE UNIT

Includes PS, PCL & XPS Controller, Automatic Duplex Unit, 500-sheet Paper Cassette, 4 GB Standard Memory, Fast Ethernet, High-speed USB 2.0 Host, 20K Toner Cartridge, and 200K Imaging Unit

### STEP 2: PAPER HANCLING OPTIONS

- PF-P21 Paper Feed Unit (500 sheets, maximum 2)
- O PF-P25 Height Adjustment Unit

#### **STEP 3: FINISHING OPTION:**

- O CS-1 Convenience Stapler
- FS-P04 Off-line Stapler



## **ACCESSORY OPTIONS FOR BIZHUB 4700I DIGITAL PRINTER**

BASE UNIT     4700i   ACTA011   4700i Printer   Includes PS, PCL & XPS Controller, Automatic Duplex Unit, 500-sheet Paper Cassette, 512 MB Standard Memory, Fast Ethernet, High-speed USB 2.0 Host, 20K Toner Yield, and 200K Imaging Unit     PAPER HANDLING OPTIONS   DK-P05   135900   Copy Desk   Adds storage and mobility. Brings printer to operational height.     PF-P21   AAJUW1   Paper Feed Unit   Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to 2. Total paper capacity. 1600 sheets     PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS   Convenience Stapler   Standalone electronic stapler.     CS-1   7640013463   Convenience Stapler   Standalone electronic stapler.     SP04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     ADJ:205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HID proximity cards.     EK-P09   ACCTWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC Interface   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK	ACCESSORIES	ITEM NO.	DESCRIPTION	NOTES
512 MB Standard Memory, Fast Ethernet, High-speed USB 2.0 Host, 20K Toner Yield, and 200K Imaging Unit     PAPER HANDLING OPTIONS     DK-P05   135900   Copy Desk   Adds storage and mobility. Brings printer to operational height.     PF-P21   AAJUW1   Paper Feed Unit   Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to 2. Total paper capacity: 1600 sheets     PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS   CS-1   7640013463   Convenience Stapler     Standalone electronic stapler.   Standalone electronic stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler     AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HID proximity cards.     EK-P08   ACCTWY1   Local Interface Rit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACHWY1   NFC interface   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface	BASE UNIT			
and 200K Imaging Unit     PAPER HANDLING OPTIONS     DK-P05   135900   Copy Desk   Adds storage and mobility. Brings printer to operational height.     PF-P21   AAJUW1   Paper Feed Unit   Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to     2. Total paper capacity: 1600 sheets     PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS     CS-1   7640013463   Convenience Stapler   Standalone electronic stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7	4700i	ACTA011	4700i Printer	Includes PS, PCL & XPS Controller, Automatic Duplex Unit, 500-sheet Paper Cassette,
PAPER HANDLING OPTIONS     DK-P05   135900   Copy Desk   Adds storage and mobility. Brings printer to operational height.     PF-P21   AAJUW1   Paper Feed Unit   Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to 2. Total paper capacity: 1600 sheets     PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS   Convenience Stapler   Standalone electronic stapler.     CS-1   7640013463   Convenience Stapler   Standalone electronic stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard				
DK-P05   135900   Copy Desk   Adds storage and mobility. Brings printer to operational height.     PF-P21   AAJUW1   Paper Feed Unit   Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to 2. Total paper capacity: 1600 sheets     PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS   CS-1   7640013463   Convenience Stapler     Standalone electronic stapler.   Standalone electronic Stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler     ADJITIONAL OPTIONS   AU-205H   R5427000136466     HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit     Provides Type A USB port. Required for installation of an authentication unit or external keyboard.   external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     Keyboard   WERTY Keyboard   QWERTY Keyboard for alphanumeric data entry.     Keyboard				and 200K Imaging Unit
PF-P21   AAJUW1   Paper Feed Unit   Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to     PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS   Exercises   Standalone electronic stapler.     CS-1   7640013463   Convenience Stapler   Standalone electronic stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     ADDITIONAL OPTIONS   Au-205H   R5427000136466   HID Multi-Card Reader     AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCWV1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     External   7640006869   QWERTY Keyboard   QWERTY Keyboard for alphanumeric data entry.     Keyboard   KH-P02   ACCFWY1   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KH-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values. <	PAPER HANDLING	OPTIONS		
PF-P25AAJUW12Height Adjustment UnitIncreases height of machine.FINISHING OPTIONSCS-17640013463Convenience StaplerStandalone electronic stapler.FS-P04AACCGWY1Off-line Electronic StaplerOff-line Electronic StaplerADDITIONAL OPTIONSAU-205HR5427000136466HID Multi-Card ReaderAllows access to SFP via HiD proximity cards.EK-P08ACCTWY1Local Interface KitProvides Type A USB port. Required for installation of an authentication unit or external keyboard.EK-P09ACCVWY1Local Interface KitProvides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.EK-P10ACCHWY1NFC interfaceProvides Near Field Communications capabilities.External7640008659QWERTY KeyboardQWERTY keyboard for alphanumeric data entry.KeyboardKeyboardKeyboard HolderKeyboard holder required for installation of external keyboard.KP-P03ACCEWY1KeypadProvides hard keys for entering numeric values.MK-P08ACCKWY1Mount KitMount kit for internal installation of AU-205H.	DK-P05	135900	Copy Desk	Adds storage and mobility. Brings printer to operational height.
PF-P25   AAJUW12   Height Adjustment Unit   Increases height of machine.     FINISHING OPTIONS   CS-1   7640013463   Convenience Stapler   Standalone electronic stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     ADDITIONAL OPTIONS   AL-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   KH-P02   ACCFWY1   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Mount Kit   Mount Kit for internal installation of AU-205H.	PF-P21	AAJUW1	Paper Feed Unit	Lower feeder unit adds 500 sheets of paper capacity (8.5" x 11" or 8.5" x 14"). Add up to
FINISHING OPTIONS     CS-1   7640013463   Convenience Stapler   Standalone electronic stapler.     FS-P04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     ADDITIONAL OPTIONS   AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     Etk-p10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     Etk-p08   ACCFWY1   Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   K   Keyboard   Reyboard.     KH-P02   ACCFWY1   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU				2. Total paper capacity: 1600 sheets
CS-17640013463Convenience StaplerStandalone electronic stapler.FS-P04AACCGWY1Off-line Electronic StaplerOff-line Electronic StaplerADDITIONAL OPTIONSAU-205HR5427000136466HID Multi-Card ReaderAllows access to SFP via HiD proximity cards.EK-P08ACCTWY1Local Interface KitProvides Type A USB port. Required for installation of an authentication unit or external keyboard.EK-P09ACCVWY1Local Interface KitProvides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.EK-P10ACCHWY1NFC interfaceProvides Near Field Communications capabilities.External7640006869QWERTY KeyboardQWERTY keyboard for alphanumeric data entry.KeyboardKeyboard HolderKeyboard holder required for installation of external keyboard.KP-P03ACCEWY1KeypadProvides hard keys for entering numeric values.MK-P08ACCKWY1Mount KitMount kit for internal installation of AU-205H.	PF-P25	AAJUW12	Height Adjustment Unit	Increases height of machine.
FS-P04   AACCGWY1   Off-line Electronic Stapler   Off-line Electronic Stapler     ADDITIONAL OPTIONS   AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.	FINISHING OPTIO	NS		
ADDITIONAL OPTIONS     AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication of an authentication of an authentication of an authentication unit or external keyboard.     EK-P09   ACCHWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.	CS-1	7640013463	Convenience Stapler	Standalone electronic stapler.
AU-205H   R5427000136466   HID Multi-Card Reader   Allows access to SFP via HiD proximity cards.     EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCHWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.	FS-P04	AACCGWY1	Off-line Electronic Stapler	Off-line Electronic Stapler
EK-P08   ACCTWY1   Local Interface Kit   Provides Type A USB port. Required for installation of an authentication unit or external keyboard.     EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication of authentication of an authentication of an authentication of an authentication of an authentication of authentication of an authentication of AUCEWY1     Keyboard   First Authentication of AUCEWY1   Mount Kit   Mount kit for internal installation of AU-205H.	ADDITIONAL OPT	IONS		
EK-P09   ACCVWY1   Local Interface Kit   Provides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keyboard.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   764006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard   Keyboard holder required for installation of external keyboard.     KH-P02   ACCFWY1   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.	AU-205H	R5427000136466	HID Multi-Card Reader	Allows access to SFP via HiD proximity cards.
EK-P09ACCVWY1Local Interface KitProvides Type A USB port and Bluetooth connectivity. Required for installation of an authentication unit or external keybaord.EK-P10ACCHWY1NFC interfaceProvides Near Field Communications capabilities.External7640006869QWERTY KeyboardQWERTY keyboard or alphanumeric data entry.KeyboardKeyboard HolderKeyboard HolderKeyboard for installation of external keyboard.KH-P02ACCFWY1Keyboard HolderKeyboard provides hard keys for entering numeric values.KP-P03ACCEWY1Mount KitMount kit for internal installation of AU-205H.	EK-P08	ACCTWY1	Local Interface Kit	Provides Type A USB port. Required for installation of an authentication unit or
authentication unit or external keybaord.     EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.				external keyboard.
EK-P10   ACCHWY1   NFC interface   Provides Near Field Communications capabilities.     External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard   Keyboard Holder   Keyboard for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.	EK-P09	ACCVWY1	Local Interface Kit	Provides Type A USB port and Bluetooth connectivity. Required for installation of an
External   7640006869   QWERTY Keyboard   QWERTY keyboard for alphanumeric data entry.     Keyboard   Keyboard     KH-P02   ACCFWY1   Keyboard Holder   Keyboard holder required for installation of external keyboard.     KP-P03   ACCEWY1   Keypad   Provides hard keys for entering numeric values.     MK-P08   ACCKWY1   Mount Kit   Mount kit for internal installation of AU-205H.				authentication unit or external keybaord.
Keyboard       KH-P02     ACCFWY1     Keyboard Holder     Keyboard holder required for installation of external keyboard.       KP-P03     ACCEWY1     Keypad     Provides hard keys for entering numeric values.       MK-P08     ACCKWY1     Mount Kit     Mount kit for internal installation of AU-205H.	EK-P10	ACCHWY1	NFC interface	Provides Near Field Communications capabilities.
KH-P02ACCFWY1Keyboard HolderKeyboard holder required for installation of external keyboard.KP-P03ACCEWY1KeypadProvides hard keys for entering numeric values.MK-P08ACCKWY1Mount KitMount kit for internal installation of AU-205H.	External	7640006869	QWERTY Keyboard	QWERTY keyboard for alphanumeric data entry.
KP-P03     ACCEWY1     Keypad     Provides hard keys for entering numeric values.       MK-P08     ACCKWY1     Mount Kit     Mount kit for internal installation of AU-205H.	Keyboard			
MK-P08 ACCKWY1 Mount Kit Mount kit for internal installation of AU-205H.	KH-P02	ACCFWY1	Keyboard Holder	Keyboard holder required for installation of external keyboard.
	KP-P03	ACCEWY1	Keypad	Provides hard keys for entering numeric values.
UK-221     ACDMWY1     Wireless LAN     Provides wireless connectivity.	MK-P08	ACCKWY1	Mount Kit	Mount kit for internal installation of AU-205H.
	UK-221	ACDMWY1	Wireless LAN	Provides wireless connectivity.

### **CONSUMABLE YIELDS**

*Based on 5% total converage		
CONSUMABLE	ITEM NO.	YIELD
TNP91 Toner – Black	ACTD031	20,000
Waste Toner Box	ACDN0Y1	32,000
IUP36K Drum Imaging Unit	AAJV01E	200,000
SK-501 Staples for FS-P04	A6Y8WY1	_
SK-602 Staples	14ҮК	-

20	bizhub 4700i Specification & Install Guide	




For complete information on Konica Minolta products and solutions, please visit: **CountOnKonicaMinolta.com** 

© 2021 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446 CountOnKonicaMinolta.com



Item #: 4700iSIG 1/2021-Z